

DIP and DOP pneumatic submersible pumps

A pneumatic pump is a great choice when failure is not an option. They're easy to use, safe and can handle almost anything you throw at them.

Application:

- Ideal for construction sites where reliable dewatering and fluid transfer are critical.
- Suitable for mining operations involving slurry, sludge, or abrasive fluids.
- Used in the process industry for handling chemicals, wastewater, and other industrial fluids.
- Deployed in municipal and utility services for sewage and clog water management.

Features:

- Safe in all environmer
- Robust technology
- Not possible to overlo
- Light lifting
- Simple design
- Plug & play



DIP (centrifugal) and DOP (membrane) pumps			DIP 25	DIP 35	DIP 65	DOP 15N	DOP 15F
Max. head		m	25	35	59	59	59
Max. flow		l/min	1680	1320	660	420	420
Max. flow		m ³ /h	100,8	79,2	39,6	25,2	25,2
Max. air requirements		l/s	70	70	70	34	34
Weight		kg	23	23	23	31	31
Dimensions: L x W x H		mm	235 x 288 x 435	235 x 288 x 435	235 x 288 x 435	390 x 330 x 585	390 x 330 x 585
Connection thread	Fluid outlet	in	G 2 ½	G 2 ½	G 2 ½	G 2 ½	G 2 ½
	Air inlet	in	G ¾	G ¾	G ¾	G ¾	G ¾
	Air outlet	in	G 1 ½	G 1 ½	G 1 ½	-	-
Part number			8492 0103 20	8492 0103 38	8492 0106 19	8492 0101 48	8492 0101 63
Part number Kit ¹⁾			8492 0103 53	8492 0103 61	8492 0106 27	8492 0101 55	

¹⁾ For the contents of the available Kits, see page 31

DIP and DOP pump Kits

Kit Item Number	Kit Description	Component in Kit	Component Description
8492 0103 53	DIP 25 Kit	8492 0103 20	DIP 25 (1x)
		3330 0034 91	Outlet hose 76 mm x 25 m incl. fittings (1x)
		8202 5102 39	Lubricator CLG-30 (black) (1x)
		3330 0032 91	Non-return valve with pipe. Thread G 1 1/2 A (1x)
8492 0103 61	DIP 35 Kit	8492 0103 38	DIP 35 (1x)
		4950 0191 90	Outlet hose 63 mm x 32 m incl. fittings (1x)
		8202 5102 39	Lubricator CLG-30 (black) (1x)
		3330 0032 91	Non-return valve with pipe. Thread G 1 1/2 A (1x)
8492 0106 27	DIP 65 Kit	8492 0106 19	DIP 65 (1x)
		4950 0191 90	Outlet hose 63 mm x 32 m incl. fittings (2x)
		8202 5102 39	Lubricator CLG-30 (black) (1x)
		3330 0032 91	Non-return valve with pipe. Thread G 1 1/2 A (1x)
8492 0101 55	DOP 15 N Kit	8492 0101 48	DOP 15 N
		4950 0191 90	Outlet hose 63 mm x 32 m incl. fittings (1x)
		8202 5102 39	Lubricator CLG-30 (black) (1x)

