

Hydraulic power packs

Features:

- Portable, compact and lightweight
- High efficiency, low noise and low fuel consumption thanks to Power On Demand function (available with selected models only)
- Low maintenance, long lifetime – moving parts move in a closed lubricated circuit
- Protective steel frame with foldable handles
- Lifting eye and cross lifting bar
- No exhaust or emission from the tools – power pack with engine can be placed away from tool
- Large return filter and replacement indicator
- Thermostatically-controlled oil cooler



Power packs		LP 9-20 P ¹⁾	LP 13-30 P ¹⁾	GP 18-30	GP 18 multiflow	LP 9-20 E
Fuel		Petrol	Petrol	Petrol	Petrol	Electric
Engine		9 HP Honda	13 HP Honda	18 HP B&S Vanguard	18 HP B&S Vanguard	5,5 kW/ 3x400 V/16A
Dry weight	kg	77	102	130	135	87
Dimensions (LxWxH)	mm	630x530x640	745x600x705	930x603x765	930x603x765	630x530x640
Oil flow	l/min	20	20-30	20-30	15-20-30-40	20
Maximum pressure	bar	150	150	172	145	150
Fuel capacity	l	6	6,5	8,5	8,5	-
Hose included		YES	YES	NO	NO	NO
Power on Demand (POD)		YES	YES	NO	NO	NO
Electric start		NO	NO	YES	YES	YES
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	101	101	101	101	96
Sound pressure level (ISO 11203)	Lp, r=1m	87	89	89	89	82
EHTMA class		C	C/D	C/D	B, C, D & E	C
Part number		1807 0080 50	1807 0110 32	1807 8000 26	1807 8000 09	1807 0080 52

¹⁾ A 7 m extension twin-hose comes as standard with LP 9-20 P, LP 13-30 P