

Underground pneumatic rock drills

Application:

- Raise driving and bolting
- Screening

Features:

- High quality, designed for production drilling
- Built-in water flushing



Rock drills		BBC 16W	BBC 34W ¹⁾	BBD 94W ¹⁾	RH 656 4W ²⁾
Hole range	mm	27-41	27-41	27-41	27-41
Weight	kg	28,5	33,5	28	22
Length	mm	705	775	670	658
Air consumption	l/s	69	88	97	48
Impact rate	blows/min	2340	2280	3300	2040
Piston diameter	mm	70	80	90	65
Stroke length	mm	55	70	45	59
Vibration level 3 axes (ISO 5349-2)	m/s ²	16,6	20,4	15	21,2
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	122	127	125	120
Sound pressure level (ISO 11203)	Lp, r=1m	111	116	114	115
Part number with shank size H 22x108 mm		8311 0401 10	8311 0408 05	8311 0206 09	8311 0302 02

Data at 6,2 bar (90 psi) air pressure

¹⁾Article will be phased out. Available until stock is exhausted.

²⁾Available only for low-regulated markets

Pneumatic rock drills – pusher legs

Application:

Underground horizontal drilling

Features:

- High quality, designed for production drilling
- Single or double telescopic pusher legs



Pusher legs		BMT 51	ALF 72D ¹⁾	ALF 72D-1 ¹⁾	BMK 62 S
Telescope		Single	Single	Single	Single
Suitable for rock drill:		BBC 16W	BBD 94W	BBD 94W	RH 656W
Feeding length	mm	1300	1300	1200	1300
Length retracted	mm	1658	1970	1830	1815
Length extracted	mm	2958	3270	3030	3115
Weight	kg	15	19	16	17
Cylinder Bore	mm	60	70	70	53
Part number		8321 0301 01	8321 0201 80	8321 0201 81	8321 0102 02

Data at 6,2 bar (90 psi) air pressure

¹⁾Article will be phased out. Available until stock is exhausted.